



www.Canopy-Wireless-Solutions.com

[Motorola Canopy Point to Multipoint 5.2 Ghz Series - Product Specifications](#)

5701SMBC Canopy 5.7 Ghz Subscriber Module Classic With AES

The SM is the subscriber termination unit or the Customer Premise Equipment (CPE). It consists of a single module that operates with an integrated 60-degree antenna. Each SM can communicate to a single AP Module at any given time. SM synchronization and control is accomplished via the received AP signal. SMs are typically located outdoor and Line of Sight (LOS) from the APs. Once the SM is initialized, it scans the Radio Frequency (RF) channels and automatically registers with the appropriate AP

- [Discount Pricing](#)
- MSRP \$845.00 Check Shopping Cart for Your Cost
- Power Supply included
- [Surge Suppressor sold Separately](#)
- Connectorized Cat 5 UV resistant Ethernet Cables Sold Separately
- [Individual Mounting Bracket Sold Separately](#)
- [27RDB 18 dB Gain Reflector Kit Sold Separately](#)
- [Canopy Subscriber Module Users Manual \(2Mb\)](#)
- [Canopy AES overview](#)

Canopy Part Number	• 5701SMBC
Description	• Canopy 5.7 Ghz Subscriber Module Classic With AES
Market Availability	• North America, Europe, South America, Asia
Signaling Rate	• 10 Mbps, 20 Mbps with Advantage AP
Typical LOS Range	• 2 mi (3.2 km), 10 mi (16 km) with reflector
Typical Aggregate Useful Throughput	• 7 Mbps
Frequency range of band	• ISM 5725-5850 MHz
Non-overlapping Channels	• 6
Channel Width	• 20 MHz
Modulation Type	• High Index 2-level and 4-level Frequency Shift Keying (FSK) optimized for interference rejection
Channel Spacing	• configurable on 5 MHz increments
Encryption	• AES capable
Latency	• 6 msec with Advantage AP, 15 msec with Canopy AP
Carrier to Interference ratio (C/I)	• ~-3dB @ 10 Mbps, ~-10dB @ 20 Mbps at -65dBm
Nominal Receiver Sensitivity (dbm typical)	• -86 dBm
Antenna Gain (dB)	• 7 dBi
EIRP (dB)	• 30 dBm (48 dBm with reflector)
Equivalent Isotropic Radiated Power (EIRP)	• 1 W (63 W with reflector)
DC Power (typical)	• 0.3 A @ 24 VDC = 7.2 W
Antenna Beam Width	• 3 dB antenna beam width 60 degrees, Azimuth and Elevation
Mean Time Between Failure (MTBF)	• 40 yr
Temperature	• -40° C to +55° C (-40° F to +131° F)
Wind Survival	• 190 km/hr (118 miles/hr)
Dimensions	• 11.75 in H x 3.4 in W x 3.4 in D (29.9 cm H x 8.6 cm W x 8.6 cm D)
Weight	• .45 kg (1 lb)
Access Method	• Time Division Duplexing/Time Division Multiple Access (TDD/TDMA)
Interface	• 10/100 Base T, half/full duplex. Rate auto negotiated (802.3 compliant)
Protocols Used	• IPV4, UDP, TCP, ICMP, Telnet, HTTP, FTP, SNMP
Network Management	• HTTP, TELNET, FTP, SNMP Version 2c
FCC ID	• ABZ89FC5804
Industry Canada Certification Number	• 109W-5700
NYCE	• 0202CE08128

Specifications subject to change without notice