



## 5.7 Ghz 43 Mbps Single End Link Integrated Antenna

**BP5730BH-1CC Canopy 5.7 GHZ, 60 Mbps OTA, Spare Backhaul, Integrated**  
Integrated Line of Sight (LOS), Near and Non Line of Sight point-to-point, medium-capacity, backhaul link with adaptive equalization, Package includes, Radio ODU, Radio IDU/Power Supply, Set of mounting hardware

- UV Rated Cat 5 PoE cable sold separately
- Surge Suppressor sold separately

- Canopy Part Number** • **BP5730BH-1CC**
- RF bands** • 5.725 GHz–5.850 GHz\*
- Channel size** • 5.8 and 5.4 GHz: 12 MHz
- Channel selection** • By Intelligent Dynamic Frequency Selection (i-DFS) or manual intervention; automatic detection on start-up and continual adaptation to avoid interference
- Transmit power control** • Adaptive, varying between 25 dBm and -10 dBm according to modulation selected and radio path\*\*
- System gain** • 5.8 and 5.4 GHz Integrated: Varies with modulation mode; up to 168 dB with 23.5 dBi integrated antenna\*\* Connectorized: Varies with modulation mode and antenna type\*\*
- Receiver sensitivity** • Adaptive, varying between -96.0 dBm and -72 dBm according to modulation selected
- Modulation** • Dynamic; 8 modes adapting between BPSK and 64 QAM
- Error correction** • FEC, ARQ
- Duplex scheme** • TDD ratio 50:50, 66:33; same or split frequency Tx/Rx
- Antenna: type/gain/B/W** • Integrated: Integrated flat plate 23 dBi / 7°
  - Connectorized: Approved to operate with flat plate up to 28 dBi or parabolic dish up to 37.7 dBi; connected via 2 x N-type female
- Range** • Up to 124 miles (200 km)\*\*\*
- Data rates Full** • 5.8 and 5.4 GHz: Up to 43 Mbps at the Ethernet; dynamically variable with modulation range from 3.0 Mbps to 43 Mbps (aggregate)
- Security and encryption** • Proprietary scrambling mechanism; optional AES 128 Bit Encryption
  - Regulatory conditions for RF bands should be confirmed prior to system purchase*
  - \*\* Gain and maximum transmit power may vary based on regulatory domain*
  - \*\*\* In all cases the range limit is set by the latest software release*
- Protocol** • IEEE 802.3
- Packet prioritization** • IEEE 802.1p
- Interface** • 10 BASE-T / 100 BASE-T (RJ-45)–auto MDI/MDIX switching
- Latency** • Throughput Mode: Less than 7 mSec (default)
  - Latency Mode: Less than 6 mSec
- LED indicators** • Power status, Ethernet link status and activity
- System management** • Web Server and SNMP
- Installation** • Built-in audio assistance for link optimization
- Connection** • Distance between outdoor unit and primary network connection: up to 330' (100 meters)
- Dimensions** • Integrated outdoor unit (ODU): Width 14.5" (370 mm), Height 14.5" (370 mm), Depth 3.75" (95 mm)
  - Connectorized ODU: Width 12" (305 mm), Height 12" (305 mm), Depth 4.1" (105 mm)
  - Powered indoor unit (PIDU Plus): Width 9.75" (250 mm), Height 1.5" (40 mm), Depth 3" (80 mm)
- Weight** • Integrated ODU: 12.1 lbs (5.5 kg) including bracket
  - Connectorized ODU: 9.1 lbs (4.3 kg) including bracket
  - PIDU Plus: 1.9 lbs (864 g)
- Wind speed** • 150 mph (242 kph)
- Power supply** • Integrated with Indoor Unit
  - 90–240 VAC, 50–60 Hz / 36-60V DC
  - 55 W max
- Operating temperature** • -40°F (-40°C) to +140°F (+60°C), including solar radiation
- Protection and safety** • IP65/ UL60950; IEC60950; EN60950; CSA-C22.2 No. 60950
- Regulatory** • 5.8 GHz: FCC Part 15, sub-part C 15.247, Eire ComReg 03/42, UK Approval to IR2007
- EMC** • USA–FCC Part 15, Class B; Europe–EN 301 489-4

*Specification subject to change without notice, check before placing orders*