

## 5.7 Ghz 150 Mbps, Spare, Connectorized Antenna



**BP5830BHC15-1CC, 5.7 GHz 150 Mbps, Spare Backhaul Unit, Connectorized Antenna**  
Connectorized Line of Sight (LOS), Near and Non Line of Sight point-to-point, high-capacity, back haul link with adaptive equalization. Package includes, Radio ODU, Radio IDU/Power Supply, Set of mounting hardware

- Formerly Orthogon Spectra
- RG-214 NMale to NMale Cable sold separately
- Flat Panel and Parabolic Antennas sold separately
- UV Rated Cat 5 PoE cable sold separately
- Software Upgradeable to 300 Mbps Aggregate at the Ethernet
- Surge Suppressor sold separately

<b>Canopy Part Number</b>	• <b>BP5830BHC15-1CC</b>
<b>RF band</b>	• 5.725 GHz–5.850 GHz*
<b>Channel size</b>	• 30 MHz
<b>Frequency control</b>	• By Intelligent Dynamic Frequency Selection (i-DFS) or manual intervention; automatic selection on start-up and continual adaptation to avoid interference; 10 MHz step size for WiMAX compatibility
<b>Transmit power control</b>	• Varies with modulation mode and settings from 0 dBm to 25 dBm
<b>System gain</b>	• Integrated: Varies with modulation mode; up to 163 dB using 23.5 dBi integrated antenna ** • Connectorized: Varies with modulation mode and antenna type**
<b>Receiver sensitivity</b>	• Adaptive, varying between -91 dBm and -58 dBm
<b>Modulation</b>	• Dynamic; adapting between BPSK single and 256 QAM dual
<b>Error correction</b>	• FEC, ARQ
<b>Duplex scheme</b>	• TDD ratio: Dynamic or Fixed; same or split frequency Tx/Rx
<b>Antenna: type/gain/B/W</b>	• Integrated: Integrated flat plate 23 dBi / 7° • Connectorized: Approved to operate with flat plate up to 28 dBi or parabolic dish up to 37.7 dBi; connected via 2 x N-type female
<b>Range</b>	• Up to 124 miles (200 km)***
<b>Security and encryption</b>	• Proprietary scrambling mechanism; optional AES 128 and 256 Bit Encryption
	* Regulatory conditions for RF bands should be confirmed prior to system purchase
	** Gain and maximum transmit power may vary based on regulatory domain
	*** In all cases the range limit is set by the latest software release
<b>Protocol</b>	• IEEE 802.3
<b>User data throughput</b>	• Integrated and Connectorized Full: Dynamically variable up to 300 Mbps at the Ethernet (aggregate) • Integrated and Connectorized Lite: Dynamically variable up to 150 Mbps at the Ethernet (aggregate)
<b>Latency</b>	• <1 ms each direction typical
<b>Interface</b>	• 10 / 100 / 1000 Base T (RJ-45) – auto MDI/MDIX, 1000 Base SX option
<b>T1/E1 Interface</b>	• G703/G704 G823/G824 • Integrated and Connectorized: Full Provides dual T1/E1 ports • Integrated and Connectorized Lite: Provides a single T1/E1 port
<b>LED indicators</b>	• Power status, Ethernet link status and activity
<b>System management</b>	• Web or SNMP using MIBII, WiMAX and private MIB
<b>Installation</b>	• Built-in audio assistance for link optimization • Connection Distance between outdoor unit and primary network connection: up to 330' (100 meters)
<b>Dimensions</b>	• Integrated outdoor unit (ODU): Width 14.5" (370 mm), Height 14.5" (370 mm), Depth 3.75" (95 mm) • Connectorized ODU: Width 12.2" (309 mm), Height 12.2" (309 mm), Depth 4.1" (105 mm) • Powered indoor unit (PIDU Plus): Width 9.75" (250 mm), Height 1.5" (40 mm), Depth 3" (80 mm)
<b>Weight</b>	• Integrated ODU: 12.1 lbs (5.5 kg) including bracket • Connectorized ODU: 9.1 lbs (4.3 kg) including bracket • PIDU Plus: 1.9 lbs (864 g)
<b>Wind speed</b>	• 150 mph (242 kph)
<b>Power supply</b>	• Integrated with Indoor Unit
<b>Power source</b>	• 90–240 VAC, 50–60 Hz / 36-60V DC; redundant powering configurations supported
<b>Power consumption</b>	• 55 W max
<b>Operating temperature</b>	• -40°F (-40°C) to +140°F (+60°C), including solar radiation
<b>Protection and safety</b>	• UL60950; IEC60950; EN60950; CSA-C22.2 No. 60950
<b>Radio</b>	• 5.8 GHz: FCC Part 15, sub-part C 15.247, Eire ComReg 03/42, UK Approval to IR2007 • 5.4 GHz: EN 301 893
<b>EMC</b>	• USA–FCC Part 15, Class B; Europe–EN 301 489-4

*Specification subject to change without notice, check before placing orders*